

Gamma GTH3 XFA



BENEFITS

- Meets the highest European classification for respiratory performance (TH3) and the defined standards for Australia and New Zealand (P2).
- Integrated LED working lights improve safety and work efficiency in dimly lit welding conditions.
- Class leading LiFE+ Color Auto-darkening welding filter makes working more convenient with extended shade selection up to level 15.
- Visible welding filter parameter selection enables working without interruptions when settings can be adjusted on the go with the remote control.
- GapView switch sets a clear view beneath the welding visor providing a 15 mm gap and a clear vision of the working area.
- Axis regulator tunes eye-line perspective.
- Heavy duty battery charged full in only 3 hours.
- 198 cm² grinding visor, 170° work site view.
- Respirator (PFU 210e) air speed selection 170 or 210 liters per minute.
- Features for added comfort and safety such as a flexible and adjustable headband, axis regulator to adjust the visor position and ClickLenz system allowing the replacement of clear lens plates in seconds.

TECHNICAL SPECIFICATIONS

Gamma GTH3 XFA

Product code	9873130
Weight	1100 g
Operating temperature	-5...+55 °C
EN 175	S-B
EN 12941	TH3
AS/NZS 1716;	P2
Welding filter	XA 74
View size	102 x 74 mm
Filter dimension	Customized
Shade range	5, 8, 9-15
ADF light state	6
ADF switching time	0.1 ms
LiFE+ Color (yes/no)	Yes
Grinding fuction (yes/no)	No

Gamma GTH3 XFA

PAPR

PFU 210